

# ViewSonic® PROJECTOR PA503W

## Key Features

- 22,000:1 contrast ratio
- SuperColor™ technology
- 5 colour modes
- Auto power off
- Vertical keystone



## Product Description

The ViewSonic PA503W offers impressive visual performance to improve presentations, ideal for use in small business meeting rooms and classrooms. Packed with 3500 ANSI Lumens of brightness and a 22,000:1 contrast ratio, this projector is guaranteed to reproduce the finest of details regardless of the amount of ambient lighting present. ViewSonic exclusive SuperColor™ technology offers a wider range of displayable color for projected images with true-to-life color accuracy. Users can choose from 5 color modes, including standard, brightest, presentation, photo, and movie mode, to select the mode that best suits their needs based on their usage scenario. In addition, the energy-saving SuperEco mode of PA503W reduces power consumption and extends the lamp life by up to 15,000 hours.



- |                    |                           |           |
|--------------------|---------------------------|-----------|
| 1. Keypad          | 8. Audio in/out           | 15. RS232 |
| 2. LED indicator   | 9. HDMI                   |           |
| 3. Lamp cover      | 10. Dual VGA              |           |
| 4. Security lock   | 11. VGA out               |           |
| 5. Zoom/Focus      | 12. Mini USB              |           |
| 6. Front IR        | 13. Video                 |           |
| 7. Projection Lens | 14. Kensington® Lock Slot |           |

Visit Us [www.viewsonic.com](http://www.viewsonic.com)

## SPECIFICATION

Native Resolution:	1280x800
DC type:	DC3
Brightness:	3500 ANSI lumens
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	200W
Lens:	F=2.56-2.68, f=22-24.1 mm
Projection Offset:	100%+/-5%
Throw Ratio:	1.55~1.70
Image size:	30" - 300"
Throw Distance:	1m-10.98m(100" @3.34m)
Keystone:	±40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Eco):	27dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

## INPUT

Computer in (share with component):	2
Composite:	1
Audio-in (3.5mm):	1
HDMI:	1 (Back)

## OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W

## CONTROL

RS232:	1
USB type mini B (Services):	1

## OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.2kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

## STANDARD ACCESSORY

Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG & CD:	QSG: 1 / CD: NA

## OPTIONAL ACCESSORY

Air Filter:	RSPL
-------------	------