

Key Features

- 25,000:1 contrast ratio
- SuperColor™ technology
- 5 color modes
- Auto power off
- Vertical keystone



Product Description

The ViewSonic SP6 offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, the projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColor™ technology offers a wider range of displayable color ensuring true-to-life color accuracy in both bright and dark environments without sacrificing image quality.



- | | | |
|--------------------|---------------------------|-----------|
| 1. Keypad | 8. Audio in/out | 15. RS232 |
| 2. LED indicator | 9. HDMI | |
| 3. Lamp cover | 10. Dual VGA | |
| 4. Security lock | 11. VGA out | |
| 5. Zoom/Focus | 12. Mini USB | |
| 6. Front IR | 13. Video | |
| 7. Projection Lens | 14. Kensington® Lock Slot | |

Visit Us www.viewsonic.com

SPECIFICATION

Native Resolution:	1024x768
Brightness:	4,800 ANSI Lumens
Contrast Ratio with SuperEco mode:	25,000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light Source Life (hours) with Normal Mode:	5000
Light Source Life (hours) with SuperEco Mode:	15000
Lamp Watt:	190W
Lens:	F=2.56-2.68, f=22-24.1 mm
Projection Offset:	120%+/-5%
Throw Ratio:	1.96-2.15
Optical Zoom:	1.1x
Digital Zoom:	0.8x-2.0x
Image size:	30" - 300"
Throw Distance:	1.19m-13.11m(100" @3.98m)
Keystone:	±40° (Vertical)
Audible Noise (Normal):	31dB
Audible Noise (Eco):	27dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K-102KHz
Vertical Scan Rate:	23-120Hz

INPUT

Computer in (share with component):	2
Composite:	1
HDMI:	1 (HDMI 1.4/ HDCP 1.4)
Audio-in (3.5mm):	1

OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W

CONTROL

RS232:	1
USB type mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0-40°C
Carton:	Brown
Net Weight:	2.2kg
Gross Weight:	3.24Kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Packing Dimensions:	365x300x188mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages
User Guide Language:	English, S-Chinese, T-Chinese, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Total 15 languages

STANDARD ACCESSORY

Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG & CD:	QSG: 1 / CD: NA

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-108
Air Filter:	RSPL
Wall/Ceiling Mount:	PJ-WMK-007
Carry Bag:	PJ-CASE-008