SKORPIO[™] X3 **OIDOJATACO**

OUTSTANDING USER INTERFACE

Equipped with the largest high-visibility color graphic display (3.2 in) with touch screen in its class, the Skorpio™ X3 mobile computer helps users work more efficiently. Three different keyboards (the 50-key alphanumeric keypad, the 38-key functional keypad and the 28-key numeric keypad) allow data to be input very quickly. Operating systems include your choice of the standard Microsoft Windows Embedded Handheld 6.5 or Windows CE 6.0.

ERGONOMIC AND RELIABLE

This rugged mobile computer is particularly suitable for mobile commerce solutions in the retail environment both on store shelves and in stock rooms. With the best ergonomics on the market, the Skorpio X3 mobile computer reduces operator fatigue with no compromise in terms of reliability and robustness, resisting harsh environments, multiple drops, strong shocks and repetitive tumbles. The pistol grip model has the most durable and comfortable handle in the industry. Its compact size and light weight combine to offer excellent balance and superior handling.

WIRELESS COMMUNICATION

The Skorpio X3 mobile computer's wireless communication capabilities (Bluetooth® EDR, IEEE 802.11 a/b/g) enable fast transactions and complete interaction with information systems including the newest RF security protocols such as WPA™ and WPA2[™]. Additionally, Cisco Compatible Extensions CCX v4 certification permits all the advantages offered by the Cisco WLAN infrastructure.

DATALOGIC'S PATENTED 'GREEN SPOT'

Skorpio X3™ mobile computers also include Datalogic's patented 'Green Spot' technology for good-read feedback. This technology projects a green spot directly on the bar code, notifying the user that a successful 'read' has occurred. Both 1D laser scanning and 2D bar code imaging configurations provide an inclined scan engine so that the display can be viewed while reading bar codes. There is no need for the user to turn the wrist in order to scan, thus making it easier to aim and faster to read.

28-key Numeric

DOATALOGIC





A R to the set of the

ODATALOGIC

141 141 141

50-key

Alphanumeric

DOATALOGIC

120

14 1.0

..... . -

FEATURES

- Large high visibility color graphic display with touch screen
- Laser scanner or wide aspect 2D imager with Datalogic's patented Green Spot technology for good-read feedback
- Compact, lightweight and robust
- Microsoft Windows Embedded Handheld 6.5 or Microsoft Windows CE 6.0 Operating System
- Summit embedded 802.11 a/b/g radio for enterprise-class mobile connectivity with CCX v4 certification
- Bluetooth[®] wireless communications 2.0 with EDR
- 1.5 m / 5.0 ft drop resistance
- IP64 protection class
- Wavelink[®] Powered[™] with pre-installed and pre-licensed Wavelink® Avalanche™
- Wavelink® Terminal Emulation pre-licensed on pistol grip models
- Pal[™] Application Library pre-licensed
- Attachable handle
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY-APPLICATIONS

- Inventory/Picking
- Shelf replenishment
- Price management
- Order entry
- Assisted sales
- Line busting
- Shipping/Receiving

SKORPIO[™] X3

DATALOGIC

S	WIRELESS COMMUNICATIONS		READING PERFORMANCE	
CIFICATIONS	LOCAL AREA NETWORK (WLAN) PERSONAL AREA NETWORK (WPAN)	Summit IEEE 802.11 a/b/g Frequency range: Country dependent, typically 2.4 GHz and 5.2 GHz; Cisco Compatible CCX v4 Security Bluetooth® wireless technology IEEE 802.15 Class 2 with EDR	IMAGING	Good Read Feedback: Datalogic's patented 'Green Spot' for good-read feedback Optical Resolution: Linear codes: 4 mils; 2D codes: 5 mils; Scan Rate: 60 frames/sec maximum Depth of Field: 3.5 to 41.5 cm / 1.4 to 16.4 in, depending on bar code density and type; Wide Aspect Imager with Datalogic's patented
	DECODING CAPABILITY			'Green Spot' technology
AL SPEC	1D / LINEAR CODES 2D CODES POSTAL CODES STACKED CODES	Auto discriminates all standard 1D codes including GS1 DataBar™linear codes. Aztec Code, Data Matrix, MaxiCode, QR Code, UPU FICS, USPS Intelligent Mail Australian Post, Japan Post, KIX Code, Planet, Postnet, Royal Mail Code (RM4SCC) Micro PDF, PDF417	LASER	Depth of Field: 4.0 to 82.0 cm / 1.5 to 32.3 in, depending on bar code density and type Good Read Feedback: Datalogic's patented 'Green Spot' for good-read feedback; Optical Resolution: 0.10 mm (4 mils); Scan Rate: 104+/- 12 scans/sec Standard Performance Laser (SPL) with Green Spot
3	STAURED CODES		SAFETY & REGULATORY	
\geq	ELECTRICAL		AGENCY APPROVALS	The product meets necessary safety and regulatory approvals for its intended use. Complies to EU RoHS VLD - Class 2 IEC/EN60825-1; Compliant with 21 CFR 1040.10 except for deviations pursuant to laser notice No. 50 dated June 24, 2007. Exempt Risk Group IEC/EN62471
TECHI	BATTERY	TERY Removable battery pack with rechargeable Li-Ion batteries. Local micro-USB connection for fast battery charging. Standard: 3.7 V; 3,000 mAh (11.1 Watt-hours) Extended: 3.7 V; 5,200 mAh (19.2 Watt-hours)	ENVIRONMENTAL COMPLIANCE LASER CLASSIFICATION	
			LED CLASSIFICATION	
			SOFTWARE	
	ENVIRONMENTAL DROP RESISTANCE PARTICULATE AND WATER SEALING TEMPERATURE	Withstands drops from 1.5 m / 5.0 ft onto concrete IP64 Operating: -10 to 50 °C / 14 to 122 °F	APPLICATIONS CONFIGURATION & MAINTENANCE	Pal™ Application Library prelicensed Wavelink Avalanche® MC prelicensed, Wavelink Avalanche® SE prelicensed, Avalanche Remote Control™, Datalogic Firmware Utility (DFU), Datalogic Desktop Utility (DDU), Datalogic Configuration Utility (DCU) Datalogic Windows SDK™, Wavelink® Studio™, MCL- Collection™, Java Virtual Machine Wavelink CE Secure, Wavelink Certificate Manager Wavelink® Terminal Emulation™ prelicensed (for Pistol Grip models only)
	5	Storage: -20 to 70 °C / -4 to 158 °F		
	INTERFACES	CES	DEVELOPMENT	
	INTERFACES	RS-232 up to 115.2 Kbps; Micro-USB port for power only, no data communication interface;	SECURITY TERMINAL EMULATION	
		Ethernet: via single dock (external module) or multiple cradle	SYSTEM	
			COPROCESSOR	Cortex-M3, 32 bit @ 72 MHz
	PHYSICAL CHARACTERISTICS		EXPANSION SLOTS MICROPROCESSOR	Micro Secure Digital slot (SDHC) up to 32 GB XScale PXA310 @ 624 MHz
	DIMENSIONS	keyboard) / 7.6 x 3.0 x 1.3 in (2.4 x 1.4 in at keyboard) Pistol Grip: 19.3 x 7.6 x 15.6 cm / 7.6 x 3.0 x 6.2 in TFT / Transflective LCD with QVGA 240 x 320 pixel resolution, LED backlight and integrated touch screen, 3.2 in diagonal 50-key full alphanumeric, 38-key functional or 28-key numeric keyboard with backlight	MEMORY OPERATING SYSTEM	Ram Memory: 256 MB Flash Memory: 512 MB (partially used for firmware and reserved data, depending on the OS) Microsoft Windows CE 6.0 with Microsoft WordPad and Internet Explorer 6.0 Microsoft Windows Embedded Handheld 6.5 with Mobile Tools: Outlook Mobile, Word Mobile, Excel Mobile, PowerPoint Mobile, One Note Mobile and Internet Explorer Mobile 6.0
	DISPLAY			
	KEYBOARD			
	WEIGHT		WARRANTY	Internet Explorer Mobile 6.0
			WARRANTY	1-Year Factory Warranty
				Caution: Laser Radiation - do not stare into beam
ES	Base Stations/Chargers 94A150031 Single Slot Dock with Spare Battery Slot (Optional Ethernet or Modem Connection)		Cases/Holsters • 94ACC0050 Holster • 94ACC0052 Rubber B	Miscellaneous • 95ACC0002 Headset VXI VR12
ACCESSORIES	(Optional Ethernet of Modern Connec • 94A150032 Four Slot Dock (Optional • 94A150034 Multi Battery Charger			

© 2012-2014 Datalogic ADC, Inc. • All rights reserved. • Protected to the fullest extent under U.S. and international laws. • Copying, or altering of this document is prohibited without express written consent from Datalogic ADC, Inc. • Product specifications are subject to change without notice. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. and the Datalogic Automatic Data Capture logo is a trademark of Datalogic S.p.A. • Skorpio, Skorpio Gun are trademarks of Datalogic Mobile S.r.I. • The Bluetooth mark and logos are owned by the Bluetooth SIG, Inc. and any use of such mark is under license • All other brand and product names are trademarks of their respective owners. DS-SKORPIOX3-EN Revision E 20140207

www.datalogic.com